

# OX BODIES



"As Strong As An Ox"®

## The Longhorn

custom steel flats and flat dump bodies

- 10' - 22' Lengths
- $\frac{3}{16}$ " Hi-Tensile Steel Floors
- 2" x 8" x  $\frac{3}{16}$ " Tube Longsills-Complete Tubing Understructure
- 10 GA Front Bulkhead with 4" Channel Supports

**THIS BODY IS  
DESIGNED TO HAUL ...**

Building Materials, Lumber,  
Palletized Loads, Equipment,  
Agricultural Loads



**Childersburg Truck Service, Inc.**

**256-378-3101**

**[www.childersburg-truck.com](http://www.childersburg-truck.com)**

# The Longhorn

## Standard Features

- 3/16" One piece floor material
- Inside or outside stake pockets with rub rail
- Federal Standard 108, all LED lights
- One year warranty
- Sherwin Williams epoxy primer and polyurethane top coat - black
- 2" x 8" x 3/16" Tubing longsills
- 1 1/2" x 3" x 11 Gauge tubing crossmembers
- 10 ga Bulkhead with vision hole and channel bracing
- Cable to pump, air-shift PTO controls
- Custom wiring harness
- 10-22 ft. length

## Basic Options

- Fixed and removable (stake or solid) sides
- Removable (stake or solid) tailgate
- Rear barn-door tailgate
- Manual pull out tarp
- Controls; all air, hot-shift PTO or any combination
- 24"-42" Cab shield
- 18" x 18" Tool boxes, 24"-60" L
- Pintle hitches
- One way or two way freight
- Twin telescopic or scissor hoists
- Tie down straps with ratchets, fixed or sliding
- Custom paint



Twin telescopic hoists (shown with tool box option)



Latch.



Adjustable ratchet tie-downs slide on rail.



HOIST LOAD CAPACITIES (IN TONS)						
BODY LENGTH (FT)	OVER-HANG (IN)	HOIST MODEL				
		TWIN TELESCOPIC			SCISSOR	
		3250	4375	5390	E-15	F-18
10	0	6.0				
	6				16.3	
	18	9.8			21.0	
	30				29.4	
12	0	4.8	8.6			
	6				13.3	
	18	6.9	13.4		16.3	
	30				21.0	
14	0		7.0	22.7		
	6				11.3	14.9
	18		9.8	32.8	13.3	17.6
	30				16.3	21.5
16	0		5.9	18.9		
	6				9.8	12.9
	18		7.7	25.3	11.3	14.9
	30				13.3	17.6
18	0			16.1		
	6				11.4	24.9
	18			20.6	12.9	28.8
	30				14.9	34.2
20	0			14.1		
	6				10.2	21.9
	18			17.4	11.4	24.9
	30				12.9	28.8
21	0					
	6				9.7	
	18				10.7	
	30				12.1	
22	0					
	6					19.5
	18					21.9
	30					24.9

## HOIST SPECIFICATIONS

	TWIN TELESCOPIC			SCISSOR		
	3250	4375	5390	E-15	F-18	6600
NTEA PERFORMANCE CLASS	C	D	H	E	F	K/110
NUMBER OF STAGES	2	3	3	1	1	3
ACTIVE STAGE SIZES(IN)	2,1	3,2,1	4,3,2	6	6	4 3/4, 3 1/2, 2 3/4
TOTAL STROKE(IN)	50	74.04	90	20.688	29.44	86
CYLINDER RATED PRESSURE(PSI)	2000	2000	2000	3250	3250	3250
STD PUMP GPM @ 1800 RPM	29	29	29	6*	10*	15*
RECOMMENDED BODY LENGTH(FT)	10-12	12-16	14-20	10-16	14-21	16-24
APPROXIMATE WEIGHT	50	85	160	430	580	1020

Specifications subject to change.

\*GPM @ 1000 RPM

Manufactured in the USA by  
Ox Bodies Brand, a division of



## Childersburg Truck Service

33790 US Highway 280  
Childersburg, AL 35044  
P: 256-378-3101  
F: 256-378-0346

Sold by: