

OX BODIES



"As Strong As An Ox"®

The Maverick

custom built square dump bodies

- Traditional square body design with 45 degree floor to side bevels
- One piece floor construction
- 2" x 8" $\frac{3}{16}$ " Tubing longsills and 1 $\frac{1}{2}$ " x 3" 11 ga. tubing crossmembers
- $\frac{3}{16}$ " Floor and tailgate, 10 ga. sides and front

THIS BODY CAN BE DESIGNED AND BUILT TO FIT ANY VOCATIONAL APPLICATION.



Childersburg Truck Service, Inc.

256-378-3101

www.childersburg-truck.com

The Maverick

Standard Features

- 8'-19' Lengths, 5-30 yard capacity
- 10 Gauge sides and front material
- 3/16" Floor material
- 3/16" Tailgate material
- Vertical side bracing
- 2" x 8" x 3/16" Tubing longsills
- 1 1/2" x 3" x 11 Gauge crossmembers
- 4" x 4" x 11 Gauge top rail
- Air operated tailgate
- 8" Board pockets
- 8"-15" Apron
- Tarp tie-down strips
- Ladders & steps at front of body
- 24"-36" Cab shield
- Front doghouse hoist
- Custom wiring harness
- Cable to pump, air-shift pto controls
- Federal standard 108, all LED lights
- One year warranty
- Sherwin Williams epoxy primer and polyurethane top coat

Basic Options

- Air operated hi-lift tailgate
- 2-Way (barn-door) tailgate
- Sub-frame type hoist
- Ribbed (horizontal braced) sides
- Electric or manual tarp
- Insulated sides & front
- Controls; all air, hot-shift pto or any combination
- Wood, steel or tread-brite aluminum side boards
- 42" Cab shield
- Heavy duty push bumper apron
- Tread-brite aluminum skirt covers
- Inverted trunnion hoist
- 1/4", 3/8", or Hardox floor
- Crossmemberless type body
- Body vibrator
- 1/2" Body liner
- Steerable or rigid lift axles, with wheels and tires optional
- One-way or two-way freight



Heavy duty push bumper apron.



Direct mount, front lift telescopic hoist.

HOIST SPECIFICATIONS

	84725UB	6382	63111	63120T	63130	63150T	63160T	73110	74135	74161
NTEA PERFORMANCE CLASS	60	70	80	90	100	100	100	110	100	110
NUMBER OF STAGES	1	3	3	3	3	3	3	3	4	4
ACTIVE STAGE SIZES(IN.)	6	5,4,3	5,4,3	5,4,3	5,4,3	5,4,3	5,4,3	6,5,4	6,5,4,3	6,5,4,3
TOTAL STROKE(IN.)	25	82	111	120	130	150	160	110	135	161
CYLINDER RATED PRESSURE(PSI)	2,000	2,000	2,000	2,000	2,000	2,000	2,000	2,000	2,000	2,000
STD.PUMP GPM @ 1800 RPM	29	29	48	48	48	48	48	48	48	48
RECOMMENDED BODY LENGTH(FT.)*	9-10	10-11	12-14	12-13	15-16	15-16	17	14	15-17	17-19
APPROXIMATE WEIGHT(LBS.)	228	250	260	270	295	290	290	335	370	405

HOIST LOAD CAPACITY IN TONS*

HOIST MODEL	NTEA CLASS	BODY LENGTH (FT.)												
		9	10	11	12	13	14	15	16	17	18	19		
84725UB UNDERBODY	60	26.4	23.1											
6382	70		32.3	28.5										
63111	80				33.3	29.7	26.2							
63120T	90				32.4	31.3								
63130	100								24.2	23.2				
63150T	100								31.2	29.0				
63160T	100										28.5			
73110	110							42.1						
74135	100								30.5	27.9	25.5			
74161	110										30.3	28.1	26.5	

Specifications subject to change.

*Capacities based on water-level load, 12" overhang, 50 degree dump angle.

*All hoists w/doghouse reservoir.

Manufactured in the USA by
Ox Bodies Brand, a division of



Childersburg Truck Service

33790 US Highway 280
Childersburg, AL 35044
P: 256-378-3101
F: 256-378-0346

Sold by: