

# OX BODIES



"As Strong As An Ox"®

## Trash Dump Bodies

- 10' - 22' Lengths
- 3/16" Hi-Tensile Steel Floors
- 2" x 8" x 3/16" Tube Longsills-Complete Tubing Understructure
- 10 GA Front Bulkhead
- 18" - 72" Side Heights  
10 GA Solid Sides
- Barn Door Rear Gate

**THIS BODY IS  
DESIGNED TO HAUL ...**

Construction Debris, Landscape  
Materials, Trash



**Childersburg Truck Service, Inc.**  
**256-378-3101**  
**[www.childersburg-truck.com](http://www.childersburg-truck.com)**

# Trash Dump Bodies

## Standard Features

- 3/16" One piece floor material
- 10 Gauge sides 18"-72" tall
- 18"-72" Tall barn door type 10 gauge tailgates
- 24"-36" Cab shield
- Federal Standard 108, all LED lights
- One year warranty
- Sherwin Williams epoxy primer and polyurethane top coat
- 2" x 8" x 3/16" Tubing longsills
- 1 1/2" x 3" x 11 Gauge tubing crossmembers
- Twin telescopic or scissor hoists
- Cable to pump, air-shift PTO controls
- Custom wiring harness
- 10-22 ft. length

## Basic Options

- Electric or manual tarp
- Controls; all air, hot-shift PTO or any combination
- 42" Cab shield
- 18" x 18" Tool boxes, 24"-60" L
- Pintle hitches
- One way or two way freight
- Custom paint colors



Tool Box



Twin Telescopic Hoist

HOIST LOAD CAPACITIES (IN TONS)							
BODY LENGTH (FT)	OVER-HANG (IN)	HOIST MODEL					
		TWIN TELESCOPIC			SCISSOR		
		3250	4375	5390	E-15	F-18	6600
10	0	6.0					
	6				16.3		
	18	9.8			21.0		
	30				29.4		
12	0	4.8	8.6				
	6				13.3		
	18	6.9	13.4		16.3		
	30				21.0		
14	0		7.0	22.7			
	6				11.3	14.9	
	18		9.8	32.8	13.3	17.6	
	30				16.3	21.5	
16	0		5.9	18.9			
	6				9.8	12.9	28.8
	18		7.7	25.3	11.3	14.9	34.2
	30				13.3	17.6	42.1
18	0			16.1			
	6					11.4	24.9
	18			20.6		12.9	28.8
	30					14.9	34.2
20	0			14.1			
	6					10.2	21.9
	18			17.4		11.4	24.9
	30					12.9	28.8
21	0						
	6					9.7	
	18					10.7	
	30					12.1	
22	0						
	6						19.5
	18						21.9
	30						24.9

HOIST SPECIFICATIONS						
	TWIN TELESCOPIC			SCISSOR		
	3250	4375	5390	E-15	F-18	6600
NTEA PERFORMANCE CLASS	C	D	H	E	F	K/110
NUMBER OF STAGES	2	3	3	1	1	3
ACTIVE STAGE SIZES(IN)	2,1	3,2,1	4,3,2	6	6	4 3/4, 3 1/2, 2 3/4
TOTAL STROKE(IN)	50	74.04	90	20.688	29.44	86
CYLINDER RATED PRESSURE(PSI)	2000	2000	2000	3250	3250	3250
STD PUMP GPM @ 1800 RPM	29	29	29	6*	10*	15*
RECOMMENDED BODY LENGTH(FT)	10 - 12	12 - 16	14 - 20	10-16	14-21	16-24
APPROXIMATE WEIGHT	50	85	160	430	580	1020

Specifications subject to change.

\*GPM @ 1000 RPM

Manufactured in the USA by  
Ox Bodies Brand, a division of



Sold by:

## Childersburg Truck Service

33790 US Highway 280  
Childersburg, AL 35044  
P: 256-378-3101  
F: 256-378-0346